











CST35

Terminal Type - CST35, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 125 A , Rated cross-section – 35 mm², connection method: Screw connection, number of connections: 2, cross-section: 10 mm² - 50 mm², mounting type: TS32

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
End Clamp		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
EPZ	Height : 52.00 mm Width : 2.50 mm Length : 58.00 mm	
Fixed Bridge		
CCLA35K-2W	Height : 27.00 mm Pitch : 17.00 mm Length : 25.50 mm	
CCLA35K-10W	Height : 27.00 mm Pitch : 17.00 mm Length : 165.00 mm	
CCLA35K-3W	Height : 27.00 mm Pitch : 17.00 mm Length : 42.50 mm	
CCLA35K-4W	Height : 27.00 mm Pitch : 17.00 mm Length : 60.00 mm	
CCLA35K-5W	Height : 27.00 mm Pitch : 17.00 mm Length : 77.50 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	
Partition Plate		
BPZ	Height : 76.00 mm Width : 3.30 mm Length : 73.00 mm	
Switching Jumper		
RSL25	Thickness : 1.60 mm Pitch : 12.00 mm Length : 21.00 mm	
LSR35		

Warning Label		
WL35	Width : 35.00 mm Thickness : 1.50 mm Length : 74.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	