










DCF4A2

Terminal Type - DCF4A2, Fuse terminal block with LED of 240 VAC for fuse failure indication, nominal voltage: 800 V, nominal current: 10 A ,Rated cross-section – 4 mm², suitable size of cartridge fuse : 5X20 mm and 5x25 mm, connection method: Spring Cage connection, number of connections: 2, cross-section: 0.5 mm² - 4 mm², mounting type: TS 35/7.5, TS 35/15

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
DFEP	Height : 56.50 mm Width : 2.50 mm Length : 66.00 mm	
Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	
Plug-in Bridge/Jumper		
SSL4	Height : 23.80 mm Width : 6.00 mm Length : 7.50 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	

Marker carriers			
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm		

