












KUDD4CA2

Terminal Type - KUDD4CA2 , Component Housings terminal block, nominal voltage: 500 V, Diode : 1N 4007 , Common Anode ,Diode current : 1 A ,Diode Reverse Voltage - 1000 V, Rated cross-section: 2.5 mm², connection method: Screw connection, number of connections: 3, cross-section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32 ,

Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPDD	Height : 50.00 mm Width : 2.50 mm Length : 54.00 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	

Marker carriers			
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm		
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm		
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm		

