


SQ6

Terminal type - SQ6 , Feed-through terminal block, nominal voltage: 1000 V, nominal current: 41 A, Rated cross section: 6 mm² , connection method: Spring Cage connection, number of connections: 2, cross section: 0.2 mm² - 10 mm², AWG: 24-8 , mounting type: TS 35/7.5, TS 35/15

Product Accessories


Cover Profile

PCPDBF-3	Height : 14.10 mm Thickness : 1.50 mm Length : 79.00 mm	
----------	---	---


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	



DIN Rail, Unperforated








CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap



CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp

SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
CSP6	Height : 29.60 mm Width : 2.00 mm Length : 64.20 mm	
Marker For Terminal Blocks		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	
Partition Plate		
DBF-3	Height : 50.00 mm Width : 3.00 mm Length : 78.00 mm	
Plug-in Bridge/Jumper		
SLPU8-2W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 15.20 mm	

Plug-in Bridge/Jumper		
SLPU8-10W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 79.20 mm	
SLPU8-3W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 23.20 mm	
SLPU8-4W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 31.20 mm	
SLPU8-5W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 39.20 mm	
SLPU8-6W	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 47.20 mm	
SLPU8-3AW	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 23.20 mm	
SLPU8-7AW	Height : 33.30 mm Width : 3.00 mm Pitch : 8.00 mm Length : 55.20 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	