


## CATM4

Terminal Type - CATM4 , Feed Through Terminal Block , nominal voltage: 1100 V, nominal current: 57 A, Rated cross-section - 10 mm<sup>2</sup>, connection method: Bolt Connection - Screw driver operated , number of connections: 2, cross-section: 2.5 mm<sup>2</sup> - 10 mm<sup>2</sup> , mounting type : TS32



### Approvals



### General Information

|                              |                                             |
|------------------------------|---------------------------------------------|
| Product Name                 | CATM4                                       |
| Connection Method            | Bolt Connection                             |
| Rating                       | 1100 V / 57 A / 10 mm <sup>2</sup> / 1.2 Nm |
| HSN Number                   | 85389000                                    |
| Standard Packing Qty (in No) | 50                                          |
| Country Of Origin            | India                                       |
| Screw thread                 | M4                                          |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 13 mm   | 0.51 inch |
| Length                      | 46 mm   | 1.81 inch |
| Height                      | 42 mm   | 1.65 inch |
| Weight of std. Packing Unit | 1.26 Kg |           |

### Material Data

|                     |                                 |
|---------------------|---------------------------------|
| Insulating Material | Melamine                        |
| Standard Colour     | Khakhi                          |
| Colour Variants     | Red, Yellow, Blue, Black, Green |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 2.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 6 mm <sup>2</sup>   |
| Conductor cross section solid min    | 2.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 6 mm <sup>2</sup>   |


### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 2.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 6 mm <sup>2</sup>   |


|                                   |                     |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 2.5 mm <sup>2</sup> |
| Conductor cross section solid max | 6 mm <sup>2</sup>   |

## Product Accessories






### Cover Profile

|          |                                                               |                                                                                     |
|----------|---------------------------------------------------------------|-------------------------------------------------------------------------------------|
| PCC3NV   | Width : 300.00 mm<br>Thickness : 1.50 mm<br>Length : 48.50 mm |  |
| PCCM26NV | Width : 26.00 mm<br>Thickness : 1.00 mm<br>Length : 45.50 mm  |  |
| PCCM39   | Width : 39.00 mm<br>Thickness : 1.00 mm<br>Length : 45.50 mm  |  |


### DIN Rail Perforated

|     |                                                              |                                                                                      |
|-----|--------------------------------------------------------------|--------------------------------------------------------------------------------------|
| CHS | Height : 15.00 mm<br>Width : 32.00 mm<br>Thickness : 1.50 mm |  |
|-----|--------------------------------------------------------------|--------------------------------------------------------------------------------------|

### End Clamp

|       |                                                            |                                                                                       |
|-------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SCS   | Height : 26.90 mm<br>Length : 21.00 mm                     |  |
| SCSN  | Height : 31.00 mm<br>Width : 8.40 mm<br>Length : 27.00 mm  |  |
| SCUP  | Height : 34.00 mm<br>Length : 44.75 mm                     |  |
| SCUSL | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm  |  |
| SCUDD | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm |  |
| SCUN  | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |  |

| End Cover                  |                                                                                   |                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| EPS4NV                     | Height : 28.50 mm<br>Width : 2.50 mm<br>Length : 46.00 mm                         |    |
| Insertion Bridge           |                                                                                   |                                                                                       |
| ADSL-2W                    | Width : 20.50 mm<br>Pitch : 13.00 mm<br>Length : 24.00 mm                         |    |
| ADSL-10W                   | Width : 124.50 mm<br>Pitch : 13.00 mm<br>Length : 24.00 mm                        |    |
| ADSL-3W                    | Width : 33.50 mm<br>Pitch : 13.00 mm<br>Length : 24.00 mm                         |    |
| ADSL-4W                    | Width : 46.50 mm<br>Pitch : 13.00 mm<br>Length : 24.00 mm                         |   |
| ADSL-7W                    | Width : 85.50 mm<br>Pitch : 13.00 mm<br>Length : 24.00 mm                         |  |
| Marker For Terminal Blocks |                                                                                   |                                                                                       |
| LABEL KN8                  | Width : 8.00 mm                                                                   |  |
| Partition Plate            |                                                                                   |                                                                                       |
| KBZF                       | Height : 65.00 mm<br>Width : 1.50 mm<br>Length : 65.00 mm                         |  |
| Marker carriers            |                                                                                   |                                                                                       |
| GMC                        | Height : 48.00 mm<br>Width : 39.00 mm<br>Thickness : 1.00 mm<br>Length : 38.00 mm |  |
| SCUDDMLH                   | Height : 71.50 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                        |  |

| Marker carriers |                                                           |                                                                                     |
|-----------------|-----------------------------------------------------------|-------------------------------------------------------------------------------------|
| SCUNMLH         | Height : 53.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm |  |

