


CATM5

Terminal Type - CATM5, Stud Type terminal block, nominal voltage: 1100 V, nominal current: 76 A, Rated cross-section - 16 mm², connection method: Bolt Connection - Screwdriver operated, number of connections: 2, cross-section: 2.5 mm² - 16 mm², mounting type : TS32



Approvals



General Information

Product Name	CATM5
Connection Method	Bolt Connection
Rating	1100 V / 76 A / 16 mm ² / 2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M5

Dimensions & Weight

Width	13 mm	0.51 inch
Length	46 mm	1.81 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	1.42 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red, Yellow, Blue, Black

Rated Conductor Size

Conductor cross section flexible min	2.5 mm ²
Conductor cross section flexible max	16 mm ²
Conductor cross section solid min	2.5 mm ²
Conductor cross section solid max	16 mm ²


Rated Conductor Size

Conductor cross section flexible min	2.5 mm ²
Conductor cross section flexible max	16 mm ²


Conductor cross section solid min	2.5 mm ²
Conductor cross section solid max	16 mm ²

Product Accessories






Cover Profile




PCC3NV	Width : 300.00 mm Thickness : 1.50 mm Length : 48.50 mm	
PCCM26NV	Width : 26.00 mm Thickness : 1.00 mm Length : 45.50 mm	
PCCM39	Width : 39.00 mm Thickness : 1.00 mm Length : 45.50 mm	

DIN Rail Perforated

CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
-----	--	--

End Clamp

SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
EPS4NV	Height : 28.50 mm Width : 2.50 mm Length : 46.00 mm	
Insertion Bridge		
ADSL-10W	Width : 124.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-2W	Width : 20.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-3W	Width : 33.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-4W	Width : 46.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-7W	Width : 85.50 mm Pitch : 13.00 mm Length : 24.00 mm	
Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	
Partition Plate		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	

Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	