


CBTM6S1

Terminal Type - CBTM6S1 , Feed Through Terminal Block, nominal voltage: 1100 V, nominal current: 125 A, Rated cross-section - 35 mm² connection method: Bolt Connection - Nut Driver Operated, number of connections: 2, cross section: 6 mm² - 35 mm² , mounting type: TS32



Approvals



General Information

Product Name	CBTM6S1
Connection Method	Bolt Connection
Rating	1100 V / 125 A / 35 mm ² / 2.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	25
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	26 mm	1.02 inch
Length	52 mm	2.05 inch
Height	41.5 mm	1.63 inch
Weight of std. Packing Unit	1.84 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red, Yellow, Blue, Black, Green

Rated Conductor Size

Conductor cross section flexible min	6 mm ²
Conductor cross section flexible max	35 mm ²
Conductor cross section solid min	6 mm ²
Conductor cross section solid max	35 mm ²

Rated Conductor Size

Conductor cross section flexible min	6 mm ²
Conductor cross section flexible max	35 mm ²







Conductor cross section solid min	6 mm ²
Conductor cross section solid max	35 mm ²

Product Accessories


DIN Rail Perforated

CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
-----	--	---


End Clamp

SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover

EPS5/6	Height : 30.50 mm Width : 3.00 mm Length : 52.00 mm	
--------	---	---

Marker For Terminal Blocks

LABEL KN8	Width : 8.00 mm	
-----------	-----------------	---

Partition Plate		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	