


## CST10

Terminal Type - CST10 , Feed Through Terminal block, nominal voltage: 800 V, nominal current: 57 A , Rated cross-section - 10 mm<sup>2</sup>, connection method: Screw connection, number of connections: 2, cross section: 0.5 mm<sup>2</sup> - 16 mm<sup>2</sup>, mounting type: TS32



### Approvals



### General Information

|                              |                                            |
|------------------------------|--------------------------------------------|
| Product Name                 | CST10                                      |
| Connection Method            | Screw Connection                           |
| Rating                       | 800 V / 57 A / 10 mm <sup>2</sup> / 1.2 Nm |
| HSN Number                   | 85389000                                   |
| Standard Packing Qty (in No) | 100                                        |
| Country Of Origin            | India                                      |
| Screw thread                 | M4                                         |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 10 mm   | 0.39 inch |
| Length                      | 40 mm   | 1.57 inch |
| Height                      | 49 mm   | 1.93 inch |
| Weight of std. Packing Unit | 2.55 Kg |           |

### Material Data

|                     |                                 |
|---------------------|---------------------------------|
| Insulating Material | Melamine                        |
| Standard Colour     | Khakhi                          |
| Colour Variants     | Red, Yellow, Blue, Black, Green |

### Rated Conductor Size









|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 10 mm <sup>2</sup>  |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 16 mm <sup>2</sup>  |





### Rated Conductor Size



|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 10 mm <sup>2</sup>  |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |


|                                   |                    |
|-----------------------------------|--------------------|
| Conductor cross section solid max | 16 mm <sup>2</sup> |
|-----------------------------------|--------------------|

## Product Accessories

| Cover Profile         |                                                               |                                                                                       |
|-----------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|
| PCK3                  | Height : 28.00 mm<br>Width : 58.35 mm<br>Thickness : 1.00 mm  |    |
| Cover Profile Carrier |                                                               |                                                                                       |
| UHDD                  | Height : 74.50 mm<br>Thickness : 2.00 mm<br>Length : 55.82 mm |    |
| DIN Rail Perforated   |                                                               |                                                                                       |
| CHS                   | Height : 15.00 mm<br>Width : 32.00 mm<br>Thickness : 1.50 mm  |    |
| End Clamp             |                                                               |                                                                                       |
| SCS                   | Height : 26.90 mm<br>Length : 21.00 mm                        |  |
| SCSN                  | Height : 31.00 mm<br>Width : 8.40 mm<br>Length : 27.00 mm     |  |
| SCUP                  | Height : 34.00 mm<br>Length : 44.75 mm                        |  |
| SCUSL                 | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm     |  |
| SCUDD                 | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm    |  |
| SCUN                  | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm     |  |

| End Cover        |                                                            |                                                                                       |
|------------------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| EPX              | Height : 48.60 mm<br>Width : 2.00 mm<br>Length : 39.60 mm  |    |
| Fixed Bridge     |                                                            |                                                                                       |
| CCLA10-2W        | Height : 20.00 mm<br>Pitch : 10.00 mm<br>Length : 17.30 mm |    |
| CCLA10-10W       | Height : 20.00 mm<br>Pitch : 10.00 mm<br>Length : 97.50 mm |    |
| CCLA10-3W        | Height : 20.00 mm<br>Pitch : 10.00 mm<br>Length : 27.30 mm |    |
| CCLA10-4W        | Height : 20.00 mm<br>Pitch : 10.00 mm<br>Length : 37.30 mm |   |
| CCLA10-5W        | Height : 20.00 mm<br>Pitch : 10.00 mm                      |  |
| CCLA10-6W        | Height : 20.00 mm<br>Pitch : 10.00 mm<br>Length : 57.40 mm |  |
| CCLA10-7W        | Height : 20.00 mm<br>Pitch : 10.00 mm<br>Length : 67.40 mm |  |
| CCLA10-8W        | Height : 20.00 mm<br>Pitch : 10.00 mm<br>Length : 77.40 mm |  |
| Insertion Bridge |                                                            |                                                                                       |
| SLC10N-2W        | Width : 17.50 mm<br>Pitch : 10.00 mm<br>Length : 26.50 mm  |  |
| SLC10N-10W       | Width : 97.50 mm<br>Pitch : 10.00 mm<br>Length : 26.50 mm  |  |

| Insertion Bridge           |                                                                                   |                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SLC10N-4W                  | Width : 37.50 mm<br>Pitch : 10.00 mm<br>Length : 26.50 mm                         |    |
| SLC10N-6W                  | Width : 57.50 mm<br>Pitch : 10.00 mm<br>Length : 26.50 mm                         |    |
| Marker For Terminal Blocks |                                                                                   |                                                                                       |
| LABEL KN10                 | Width : 10.00 mm                                                                  |    |
| Partition Plate            |                                                                                   |                                                                                       |
| BPX                        | Height : 60.00 mm<br>Width : 3.00 mm<br>Length : 55.00 mm                         |    |
| KBXF                       | Height : 53.40 mm<br>Thickness : 1.50 mm<br>Length : 54.00 mm                     |   |
| Switching Jumper           |                                                                                   |                                                                                       |
| LSR10-16                   | Width : 6.00 mm                                                                   |  |
| RSL10                      | Thickness : 1.60 mm<br>Pitch : 10.00 mm<br>Length : 17.00 mm                      |  |
| Warning Label              |                                                                                   |                                                                                       |
| WL10                       | Width : 28.00 mm<br>Thickness : 1.50 mm<br>Length : 39.00 mm                      |  |
| Marker carriers            |                                                                                   |                                                                                       |
| GMC                        | Height : 48.00 mm<br>Width : 39.00 mm<br>Thickness : 1.00 mm<br>Length : 38.00 mm |  |
| SCUDDMLH                   | Height : 71.50 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                        |  |

| Marker carriers |                                                           |                                                                                     |
|-----------------|-----------------------------------------------------------|-------------------------------------------------------------------------------------|
| SCUNMLH         | Height : 53.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm |  |

