


## CST16

Terminal Type - CST16, Feed Through Terminal block, nominal voltage: 800 V, nominal current: 76 A , Rated cross-section - 16 mm<sup>2</sup>, connection method: Screw connection, number of connections: 2, cross-section: 6 mm<sup>2</sup> - 25 mm<sup>2</sup>, mounting type: TS32



### Approvals



### General Information

|                              |                                            |
|------------------------------|--------------------------------------------|
| Product Name                 | CST16                                      |
| Connection Method            | Screw Connection                           |
| Rating                       | 800 V / 76 A / 16 mm <sup>2</sup> / 1.2 Nm |
| HSN Number                   | 85389000                                   |
| Standard Packing Qty (in No) | 50                                         |
| Country Of Origin            | India                                      |
| Screw thread                 | M4                                         |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 12 mm   | 0.47 inch |
| Length                      | 45 mm   | 1.77 inch |
| Height                      | 55 mm   | 2.17 inch |
| Weight of std. Packing Unit | 2.54 Kg |           |

### Material Data

|                     |                                 |
|---------------------|---------------------------------|
| Insulating Material | Melamine                        |
| Standard Colour     | Khakhi                          |
| Colour Variants     | Red, Yellow, Blue, Black, Green |

### Rated Conductor Size

|                                      |                    |
|--------------------------------------|--------------------|
| Conductor cross section flexible min | 6 mm <sup>2</sup>  |
| Conductor cross section flexible max | 16 mm <sup>2</sup> |
| Conductor cross section solid min    | 6 mm <sup>2</sup>  |
| Conductor cross section solid max    | 25 mm <sup>2</sup> |


### Rated Conductor Size

|                                      |                    |
|--------------------------------------|--------------------|
| Conductor cross section flexible min | 6 mm <sup>2</sup>  |
| Conductor cross section flexible max | 16 mm <sup>2</sup> |
| Conductor cross section solid min    | 6 mm <sup>2</sup>  |

|                                   |                    |
|-----------------------------------|--------------------|
| Conductor cross section solid max | 25 mm <sup>2</sup> |
|-----------------------------------|--------------------|

## Product Accessories


### Cover Profile

|      |                                                              |                                                                                     |
|------|--------------------------------------------------------------|-------------------------------------------------------------------------------------|
| PCK3 | Height : 28.00 mm<br>Width : 58.35 mm<br>Thickness : 1.00 mm |  |
|------|--------------------------------------------------------------|-------------------------------------------------------------------------------------|






### Cover Profile Carrier



|      |                                                               |                                                                                     |
|------|---------------------------------------------------------------|-------------------------------------------------------------------------------------|
| UHDD | Height : 74.50 mm<br>Thickness : 2.00 mm<br>Length : 55.82 mm |  |
|------|---------------------------------------------------------------|-------------------------------------------------------------------------------------|




### DIN Rail Perforated

|     |                                                              |                                                                                     |
|-----|--------------------------------------------------------------|-------------------------------------------------------------------------------------|
| CHS | Height : 15.00 mm<br>Width : 32.00 mm<br>Thickness : 1.50 mm |  |
|-----|--------------------------------------------------------------|-------------------------------------------------------------------------------------|

### End Clamp

|       |                                                            |                                                                                       |
|-------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SCS   | Height : 26.90 mm<br>Length : 21.00 mm                     |  |
| SCSN  | Height : 31.00 mm<br>Width : 8.40 mm<br>Length : 27.00 mm  |  |
| SCUP  | Height : 34.00 mm<br>Length : 44.75 mm                     |  |
| SCUSL | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm  |  |
| SCUDD | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm |  |
| SCUN  | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |  |

| End Cover                  |                                                             |                                                                                       |
|----------------------------|-------------------------------------------------------------|---------------------------------------------------------------------------------------|
| EPY                        | Height : 41.90 mm<br>Width : 2.50 mm<br>Length : 44.90 mm   |    |
| Fixed Bridge               |                                                             |                                                                                       |
| CCLA16-2W                  | Height : 20.00 mm<br>Pitch : 12.00 mm<br>Length : 21.00 mm  |    |
| CCLA16-10W                 | Height : 20.00 mm<br>Pitch : 12.00 mm<br>Length : 117.00 mm |    |
| CCLA16-3W                  | Height : 20.00 mm<br>Pitch : 12.00 mm<br>Length : 33.00 mm  |    |
| CCLA16-4W                  | Height : 20.00 mm<br>Pitch : 12.00 mm<br>Length : 45.00 mm  |   |
| CCLA16-5W                  | Height : 20.00 mm<br>Pitch : 12.00 mm<br>Length : 57.00 mm  |  |
| CCLA16-6W                  | Height : 20.00 mm<br>Pitch : 12.00 mm<br>Length : 69.00 mm  |  |
| Marker For Terminal Blocks |                                                             |                                                                                       |
| LABEL KN10                 | Width : 10.00 mm                                            |  |
| Partition Plate            |                                                             |                                                                                       |
| BPY                        | Height : 66.00 mm<br>Width : 3.00 mm<br>Length : 65.00 mm   |  |
| KBZF                       | Height : 65.00 mm<br>Width : 1.50 mm<br>Length : 65.00 mm   |  |

| Switching Jumper |                                                                                   |                                                                                       |
|------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| LSR10-16         | Width : 6.00 mm                                                                   |    |
| RSL16            | Thickness : 1.60 mm<br>Pitch : 12.00 mm<br>Length : 21.00 mm                      |    |
| Warning Label    |                                                                                   |                                                                                       |
| WL16             | Width : 30.00 mm<br>Thickness : 1.50 mm<br>Length : 50.00 mm                      |    |
| Marker carriers  |                                                                                   |                                                                                       |
| GMC              | Height : 48.00 mm<br>Width : 39.00 mm<br>Thickness : 1.00 mm<br>Length : 38.00 mm |    |
| SCUDDMLH         | Height : 71.50 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                        |  |
| SCUNMLH          | Height : 53.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm                         |  |