



## DCF4A2

Terminal Type - DCF4A2, Fuse terminal block with LED of 240 VAC for fuse failure indication, nominal voltage: 800 V, nominal current: 10 A, Rated cross-section – 4 mm<sup>2</sup>, suitable size of cartridge fuse : 5X20 mm and 5x25 mm, connection method: Spring Cage connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

|                              |                                  |
|------------------------------|----------------------------------|
| Product Name                 | DCF4A2                           |
| Connection Method            | Spring Cage Connection           |
| Rating                       | 800 V / 10 A / 4 mm <sup>2</sup> |
| HSN Number                   | 85389000                         |
| Standard Packing Qty (in No) | 50                               |
| Country Of Origin            | India                            |
| Screw thread                 | -                                |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 8 mm    | 0.31 inch |
| Length                      | 60 mm   | 2.36 inch |
| Height                      | 66.6 mm | 2.62 inch |
| Weight of std. Packing Unit | 1 Kg    |           |

### Material Data

|                     |                                         |
|---------------------|-----------------------------------------|
| Insulating Material | Polyamide 6,6                           |
| Standard Colour     | Gray                                    |
| Colour Variants     | Red, Yellow, Blue, Black, Green, Khakhi |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 4 mm <sup>2</sup>   |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 4 mm <sup>2</sup>   |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 4 mm <sup>2</sup>   |


|                                   |                     |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max | 4 mm <sup>2</sup>   |

## Product Accessories


### DIN Rail Perforated

|       |                                                                                      |                                                                                     |
|-------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| CHKDS | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |  |
| CHKS  | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |




### DIN Rail, Unperforated








|      |                                                              |                                                                                      |
|------|--------------------------------------------------------------|--------------------------------------------------------------------------------------|
| CHKD | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm |   |
| CHK  | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm  |  |

### End Cap

|           |                                                           |                                                                                       |
|-----------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKENDCAP | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm |  |
|-----------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|

### End Clamp

|        |                                                            |                                                                                       |
|--------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SCUP   | Height : 34.00 mm<br>Length : 44.75 mm                     |  |
| SCEC35 | Height : 31.50 mm<br>Width : 8.00 mm<br>Length : 45.80 mm  |  |
| SCUSL  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm  |  |
| SCUDD  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm |  |

| End Clamp                  |                                                            |                                                                                       |
|----------------------------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| DCKN                       | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm  |    |
| DCKN10                     | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |    |
| SCKN                       | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm  |    |
| SCUN                       | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |    |
| End Cover                  |                                                            |                                                                                       |
| DFEP                       | Height : 56.50 mm<br>Width : 2.50 mm<br>Length : 66.00 mm  |   |
| Marker For Terminal Blocks |                                                            |                                                                                       |
| LABEL KN8                  | Width : 8.00 mm                                            |  |
| Plug-in Bridge/Jumper      |                                                            |                                                                                       |
| SSL4                       | Height : 23.80 mm<br>Width : 6.00 mm<br>Length : 7.50 mm   |  |
| Marker carriers            |                                                            |                                                                                       |
| SCUDDMLH                   | Height : 71.50 mm<br>Width : 10.00 mm<br>Length : 55.60 mm |  |
| SCUNMLH                    | Height : 53.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |  |
| DCKNMLH                    | Height : 45.50 mm<br>Width : 6.00 mm<br>Length : 43.50 mm  |  |

| Marker carriers |                                                           |  |                                                                                     |
|-----------------|-----------------------------------------------------------|--|-------------------------------------------------------------------------------------|
| SCKNMLH         | Height : 45.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm |  |  |

