


KBTM5-15C

Terminal Type - KBTM5-15C , Feed Through Terminal Block with hinged covers , nominal voltage: 800 V (Tested at 1100 V) , nominal current: 76 A, Rated Cross Section: 16 mm² connection method: Bolt Connection - Nut driver Operated, number of connections: 2, cross section: 0.5 mm² - 16 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	KBTM5-15C
Connection Method	Bolt Connection
Rating	800 V / 76 A / 16 mm ² / 2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	INDIA
Screw thread	M5

Dimensions & Weight

Width	16.5 mm	0.65 inch
Length	50 mm	1.97 inch
Height	41.4 mm	1.63 inch
Weight of std. Packing Unit	1.3 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	16 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	16 mm ²


Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	16 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	16 mm ²

Product Accessories

Cover Profile

PCC3K	Height : 17.50 mm Width : 50.00 mm Thickness : 1.50 mm	
PCCM45K	Height : 13.15 mm Width : 45.00 mm Thickness : 1.30 mm	
PCCM30K	Height : 3.00 mm Width : 30.00 mm Thickness : 1.00 mm	


DIN Rail Perforated










CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	






DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPS4	Height : 32.00 mm Width : 1.50 mm Length : 50.00 mm	
Insertion Bridge		
KSL5-10W	Width : 142.50 mm Pitch : 15.00 mm Length : 26.50 mm	
KSL5-2W	Width : 37.50 mm Pitch : 15.00 mm Length : 26.00 mm	

Insertion Bridge		
KSL5-3W	Width : 22.50 mm Pitch : 15.00 mm Length : 26.00 mm	
KSL5-4W	Width : 52.50 mm Pitch : 15.00 mm Length : 26.00 mm	
KSL5-5W	Width : 67.50 mm Pitch : 15.00 mm Length : 26.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Partition Plate		
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	