



SCF6

Terminal Type - SCF6, Fuse Terminal block, nominal voltage: 800 V, nominal current: 10 A , Rated cross-section – 6 mm², suitable size of cartridge fuse: 5X20 mm, connection method: Spring Cage Connection, number of connections: 2, cross-section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SCF6
Connection Method	Spring Cage Connection
Rating	800 V / 10 A / 6 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	13 mm	0.51 inch
Length	62 mm	2.44 inch
Height	59.7 mm	2.35 inch
Weight of std. Packing Unit	1.46 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²


Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Product Accessories


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	




DIN Rail, Unperforated








CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp

SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
SFEP6	Height : 38.30 mm Width : 1.50 mm Length : 62.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Plug-in Bridge/Jumper		
SSL6	Height : 24.60 mm Width : 8.00 mm Length : 8.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	

Marker carriers			
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm		

