


SPT240XL

Terminal Type – SPT240XL , High current connectors with secured hinged cover , nominal voltage: 1000 V AC/1500 V DC, nominal current: 415 A, connection method: Bolt connection , Bolt with clinched conical , number of connections: 2, cross section: 25 mm² – 240 mm² , 8 AWG-600 KCMIL, mounting type: TS 35/7.5 and TS 35/15



Approvals



General Information

Product Name	SPT240XL
Connection Method	Bolt Connection
Rating	1000 V / 415 A / 240 mm ² / 14 Nm
HSN Number	85389000
Standard Packing Qty (in No)	5
Country Of Origin	India
Screw thread	M12

Dimensions & Weight

Width	55 mm	2.17 inch
Length	286.8 mm	11.29 inch
Height	89.3 mm	3.52 inch
Weight of std. Packing Unit	2.8 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	25 mm ²
Conductor cross section flexible max	240 mm ²
Conductor cross section solid min	25 mm ²
Conductor cross section solid max	240 mm ²

Rated Conductor Size

Conductor cross section flexible min	25 mm ²
Conductor cross section flexible max	240 mm ²

Conductor cross section solid min	25 mm ²
Conductor cross section solid max	240 mm ²

Ratings - CSA


CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	1000 V
B - CSA Nominal Current I _N	420 A
B - CSA Wire Min	8 AWG
B - CSA Wire Max	600 KCMIL

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	1000 V
B - UL Nominal Current I _N	420 A
B - UL Wire Min	8 AWG
B - UL Wire Max	600 KCMIL

Product Accessories


DIN Rail Perforated







CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
Fixed Bridge		
CCLASPT240-2W	Width : 35.00 mm Thickness : 3.20 mm Pitch : 55.00 mm Length : 95.00 mm	
CCLASPT240-3W	Width : 35.00 mm Thickness : 3.20 mm Pitch : 55.00 mm Length : 150.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 41.50 mm	
GMH 20	Height : 51.00 mm Width : 20.00 mm Length : 41.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	