


## SQECD-9W

Terminal Type - SQECD , PCB Connector, Stack of 9 terminals with end cover, nominal voltage: 250 V, nominal current: 15 A, Pitch: 5.08 mm, connection method: Spring Cage connection, number of connections: 9 , cross-section: 0.5 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 24 - 12, mounting type - Printed circuit board (PCB)



### Approvals



### General Information

|                              |                                           |
|------------------------------|-------------------------------------------|
| Product Name                 | SQECD-9W                                  |
| Connection Method            | Spring Cage Connection                    |
| Rating                       | 250 V / 15 A / 2.5 mm <sup>2</sup> / - Nm |
| HSN Number                   | 85389000                                  |
| Standard Packing Qty (in No) | 100                                       |
| Country Of Origin            | India                                     |
| Screw thread                 | NA                                        |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 46.7 mm | 1.84 inch |
| Length                      | 15.4 mm | 0.61 inch |
| Height                      | 14.2 mm | 0.56 inch |
| Weight of std. Packing Unit | 1.2 Kg  |           |

### Material Data

|                     |               |
|---------------------|---------------|
| Insulating Material | Polyamide 6,6 |
| Standard Colour     | Gray          |
| Colour Variants     | -             |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 2.5 mm <sup>2</sup> |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 2.5 mm <sup>2</sup> |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 2.5 mm <sup>2</sup> |

|                                   |                     |
|-----------------------------------|---------------------|
| Conductor cross section solid min | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max | 2.5 mm <sup>2</sup> |

## Product Accessories

| End Cover |                                                               |                                                                                     |
|-----------|---------------------------------------------------------------|-------------------------------------------------------------------------------------|
| SQECDP    | Height : 14.20 mm<br>Thickness : 1.00 mm<br>Length : 15.40 mm |  |

