



SQF4AD240V

Terminal Type - SQF4AD240V , Fuse Terminal block, nominal voltage: 1000 V, nominal current: 6.3 A, Rated cross section: 4.0 mm², suitable size of cartridge fuse : 5X20 mm with LED for 240V AC/V DC, connection method: Spring Cage connection, number of connections: 2, cross section: 0.08 mm² - 6 mm², AWG: 24-10 , mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SQF4AD240V
Connection Method	Spring Cage Connection
Rating	1000 V / 6.3 A / 4 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	6 mm	0.24 inch
Length	62.4 mm	2.46 inch
Height	61.2 mm	2.41 inch
Weight of std. Packing Unit	1.74 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	6 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²

Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	6 mm ²

Product Accessories

Cover Profile

PCPDBF-6	Height : 14.10 mm Thickness : 1.50 mm Length : 85.50 mm	
----------	---	---

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated




CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap



CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp

SCUP	Height : 34.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	
Partition Plate		
DBF-6	Height : 81.50 mm Width : 3.00 mm Length : 85.00 mm	
Plug-in Bridge/Jumper		
SLPU6-2W	Height : 26.00 mm Width : 10.15 mm Pitch : 6.00 mm	
SLPU6-10W	Height : 26.00 mm Width : 58.15 mm Pitch : 6.00 mm	
SLPU6-3W	Height : 26.00 mm Width : 16.15 mm Pitch : 6.00 mm	

Plug-in Bridge/Jumper			
SLPU6-4W	Height : 26.00 mm Width : 22.15 mm Thickness : 2.50 mm Pitch : 6.25 mm		
SLPU6-5W	Height : 26.00 mm Width : 28.15 mm Pitch : 6.00 mm		
SLPU6-6W	Height : 26.00 mm Width : 34.15 mm Pitch : 6.00 mm		

Marker carriers			
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm		
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm		
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm		
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm		