



PS8M-8W

Terminal Type - PS8M - 8W , Plug & socket type terminal block , nominal voltage: 800 V , nominal current: 32 A, connection method: Screw clamp connection , number of connections: 16 , Rated cross section: 6 mm², cross section: 0.5 mm² - 6 mm², mounting type: TS35/7.5 , TS35/15



Approvals



General Information

Product Name	PS8M-8W
Connection Method	Screw Connection
Rating	800 V/32 A/6 mm ² /0.8 Nm
HSN Number	85389000
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	66.16 mm	2.6 inch
Length	78.9 mm	3.11 inch
Height	44.01 mm	1.73 inch
Weight of std. Packing Unit	1.29 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	32 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

