



SGQ16

Terminal Type - SGQ 16 , Ground Modular terminal block, connection method: Spring Cage Connection, Rated cross-section: 16 mm², number of connections: 2, cross-section: 0.2 mm² - 25 mm², AWG: 24-4, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SGQ16
Connection Method	Spring Cage Connection
Rating	NAP V/NAP A/16 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	12 mm	0.47 inch
Length	82.98 mm	3.27 inch
Height	50.5 mm	1.99 inch
Weight of std. Packing Unit	2.3 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	16 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	25 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage U_n	NAP V
Nominal Current I_n	NAP A
Nominal cross section	16 mm ²
Short-time current	1.92 kA
Rated surge voltage	0 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	16 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	V
B - CSA Nominal Current I_N	A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	4 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	V
B - UL Nominal Current I_N	A
B - UL Wire Min	24 AWG
B - UL Wire Max	4 AWG