


SQECDD

Terminal Type - SQECDD , PCB Connector , nominal voltage: 250 V, nominal current: 15 A, connection method: Spring Cage connection, number of connections: 2 , cross section: 0.5 mm² - 2.5 mm², AWG: 24 - 12, width: 5.08 mm , mounting type - Printed circuit board (PCB)



Approvals



General Information

Product Name	SQECDD
Connection Method	Spring Cage Connection
Rating	250 V/15 A/2.5 mm ² / Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NA

Dimensions & Weight

Width	5.08 mm	0.2 inch
Length	22.1 mm	0.87 inch
Height	29 mm	1.14 inch
Weight of std. Packing Unit	0.36 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-4
Nominal Voltage U_n	250 V
Nominal Current I_n	15 A
Nominal cross section	2.5 mm ²
Short-time current	NAV kA
Rated surge voltage	4 kV
Degree of pollution	3

