



SQECDDWP

Terminal Type - SQECDDWP , PCB Connector Without Stacking pins , nominal voltage: 250 V, nominal current: 15 A, Rated cross section: 2.5 mm² , connection method: Spring Cage connection, number of connections: 2, cross section: 0.5 mm² - 2.5 mm², AWG: 24 - 12, mounting type - Printed circuit board (PCB)



Approvals



General Information

Product Name	SQECDDWP
Connection Method	Spring Cage Connection
Rating	250 V/15 A/2.5 mm ² / Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NA

Dimensions & Weight

Width	5.08 mm	0.2 inch
Length	22.1 mm	0.87 inch
Height	25.5 mm	1 inch
Weight of std. Packing Unit	0.35 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-4
Nominal Voltage U_n	250 V
Nominal Current I_n	15 A
Nominal cross section	2.5 mm ²
Short-time current	NAV kA
Rated surge voltage	4 kV
Degree of pollution	3

